





# tank 5l 10l 20l 25l



## technical data sheet

<b>product</b>	Sumus® tank for exhausted vegetable oils, exhausted mineral oils and also dangerous liquids.
<b>materials</b>	Coextrusion in three layers of polyethylene with not less than 70% of <b>Rilene®</b> contained between two layers of virgin polymer.
<b>tappo</b>	Standard DIN <b>51/55 mm</b> black screw-type, <b>suitable for food contact with EPE seal</b> . Closing torque 7 Nm. Upon request we are available to evaluate different types of cap and nozzle.
<b>customization</b>	On request and based on quantity.
<b>certifications</b>	<b>IPPR</b> "Second Life Plastic" <b>ADR</b>

technical data	5l 	10l 	20l 	25l 
<b>real Capacity near the mouth [l]</b>	~ 6	~ 11,6	~ 24,3	~ 28
<b>dimensions</b>	14,5 <sub>x</sub> 19,6 h 25,5	19,1 <sub>x</sub> 122,1 h 32,2	24,4 <sub>x</sub> 29,3 h 39,6	29,2 <sub>x</sub> 24,5 h 44,5
<b>weight [g]</b>	230 ÷ 250	430 ÷ 450	900	1050
<b>pallet</b>	dim.100 <sub>x</sub> 120 h 129 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 <sub>x</sub> 120 h 260 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 <sub>x</sub> 120 h 282 cap 100% regenerated pallet in recycled wood n° 112 tanks	dim.100 <sub>x</sub> 120 h 282 cap 100% regenerated pallet in recycled wood n° 96 tanks

l = litres | size in cm



**PLEASE NOTE:**  
 All information on the packaging may undergo changes due to production needs or specific agreements with **Sumus® Italia Srl**

