



5l 10l 20l 25l tank



technical data sheet

product	Sumus® tank for exhausted vegetable oils, exhausted mineral oils and also dangerous liquids.
materials	Coextrusion in three layers of polyethylene with not less than 70% of Rilene® contained between two layers of virgin polymer.
tappo	Standard DIN 51/55 mm black screw-type, suitable for food contact with EPE seal . Closing torque 7 Nm. Upon request we are available to evaluate different types of cap and nozzle.
customization	On request and based on quantity.

certifications	IPPR "Second Life Plastic" ADR		
-----------------------	---	---	---

technical data	5l 	10l 	20l 	25l 
-----------------------	---	--	--	--

real Capacity near the mouth [l]	~ 6	~ 11,6	~ 24,3	~ 28
dimensions	14,5 _x 19,6 h 25,5	19,1 _x 122,1 h 32,2	24,4 _x 29,3 h 39,6	29,2 _x 24,5 h 44,5
weight [g]	230 ÷ 250	430 ÷ 450	900	1050
pallet	dim.100 _x 120 h 129 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 _x 120 h 260 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 _x 120 h 282 cap 100% regenerated pallet in recycled wood n° 112 tanks	dim.100 _x 120 h 282 cap 100% regenerated pallet in recycled wood n° 96 tanks

l = litres | size in cm