





tank 5l 10l 20l 25l



technical data sheet

product	Sumus® tank for exhausted vegetable oils, exhausted mineral oils and also dangerous liquids.
materials	Coextrusion in three layers of polyethylene with not less than 70% of Rilene® contained between two layers of virgin polymer.
tappo	Standard DIN 51/55 mm black screw-type, suitable for food contact with EPE seal . Closing torque 7 Nm. Upon request we are available to evaluate different types of cap and nozzle.
customization	On request and based on quantity.
certifications	IPPR "Second Life Plastic" ADR

technical data	5l 	10l 	20l 	25l 
real Capacity near the mouth [l]	~ 6	~ 11,6	~ 24,3	~ 28
dimensions	14,5 _x 19,6 h 25,5	19,1 _x 122,1 h 32,2	24,4 _x 29,3 h 39,6	29,2 _x 24,5 h 44,5
weight [g]	230 ÷ 250	430 ÷ 450	900	1050
pallet	dim.100 _x 120 h 129 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 _x 120 h 260 cap 100% regenerated pallet in recycled wood n° 200 tanks	dim.100 _x 120 h 282 cap 100% regenerated pallet in recycled wood n° 112 tanks	dim.100 _x 120 h 282 cap 100% regenerated pallet in recycled wood n° 96 tanks

l = litres | size in cm